



NTSWG #
CNSS-B-07-2010

VoIP

OSI - GSA Schedule Provider
Federal Technologies, Inc. #GS-35F-0526M

Product Code:
DTD-7965-TSGB

TSG Class B Approved Cisco 7965G VoIP Phone

Key Features

- Fiber versions available*
- 5-inch TFT color display with backlight
- Supports a built-in 10/100/1000 Ethernet switch for PC connection
- Compatible with both IEEE 802.3af and 802.3at switch blades
- Meets CNSS 5001 defined requirements for use in SCIF and SAPF environments
- Class B Type Acceptance

Additional Features

- The speakerphone function is enabled and protected with the TSG on-hook security. It can be administratively disabled via the Unified Communications Manager.
- The headset port is enabled and protected with the TSG on-hook security.



The TSG Approved Cisco 7965G VoIP Class B certified phone is approved for use in SCADA, SCIF, and SAPF environments and allows the on-hook security features to be engaged while in a call providing enhanced Hold and Mute security. To meet TSG requirements, the soft-key HOLD feature must be disabled at the Call Manager. This modified phone operates normally with all versions of Cisco Unified Communications manager, Cisco Unified CallManager, and all other network devices providing unrestricted deployment and management.

Available Combinations

Part Numbers

DTD-79XX-OPT2

Description

Upgrade DTD-7965-TSGB to 100 Mbps LC Fiber SFPs for LAN and PC ports. Includes (2) DTD-SFP-FE modules and custom phone supply

DTD-79XX-OPT3

Upgrade DTD-7965-TSGB to 1 Gbps LC Fiber SFPs for LAN and PC port. Includes (2) DTD-SFP-GE modules and custom phone supply



Handset and Headset

Wideband handset
Headset port
Optional Push to Talk handset
Optional Push to Mute handset

Speakerphone

Full-duplex speakerphone with acoustic echo cancellation

LAN and PC Ports

2-port Ethernet switch (connects phone and PC over a single line)
LAN Port 10/100/1000Mb RJ45
PC Port 10/100/1000Mb RJ45

Keys

Line keys, messages, settings, services, help, speakerphone, mute, headset, navigation cluster, select, display, volume control

Dimensions (H x W x D)

6.5" x 10.375" x 7.0"

Weight

3.15 lbs.

Temperatures

Operating 32 to 104° F (0 to 40° C)
Non-operating 14 to 140° F (-10 to 60° C)

Humidity

Operating 10 to 95% , noncondensing

Power

Optional AC power supply (120/240V)

Cisco Unified Communications Manager

4.1(3)sr5b, 4.2(3)sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater

Backlit indicators

Line keys, select key, message waiting, audio path keys (handset, headset, and speakerphone)

Protocol and Standard Support

Skinny Client Control Protocol (SCCP), Session Initiation Protocol (SIP) for signaling, Dynamic Host Configuration Protocol (DHCP) client or static configuration, Trivial File Transfer Protocol (TFTP)

Security

Positive device identity through X.509v3 Certificates, digitally signed images, cryptographically secure provisioning, and secure signaling and secure media with AES-128. Cryptography is not enabled by default and may only be enabled through a cryptographically enabled CUCM. The phone also contains an 802.1X supplicant and supports EAPOL pass-through.

Licensing

The Cisco 7965G requires the purchase of a phone technology license in order to connect to the Cisco Unified Communications Manager. **Sold separately.**

Warranty

Standard 1 year parts and labor
Optional 3 year parts and labor

Options

Part Numbers

DTD-79XX-PTT
DTD-79XX-PTM
DTD-TPES61
DTD-CP791X-STAND
DTD-CP791X-STAND2

Item Description

Push to Talk handset
Push to Mute handset
Power Supply
Expansion Module Mounting (single)
Expansion Module Mounting (double)

Contact us

GLOBAL HEADQUARTERS

CIS Secure Computing
43671 Trade Center Place, Suite 142
Dulles, VA 20166

Phone: 703-996-0500

Fax: 703-996-1111

eFax: fax@cissecure.com

<http://www.cissecure.com>