



NTSWG #
CNSS-B-02-2014

VoIP

OSI - GSA Schedule Provider
Federal Technologies, Inc.
#GS-35F-0526M

Product Code:
DTD-CX600-TSGB

TSG Class B Approved Polycom CX600 Microsoft Lync PoE VoIP Phone

Key Features

- 3.5-inch, QVGA TFT 24-bit color display
- Supports a built-in 10/100/1000 Ethernet switch for PC connection
- Compatible with both IEEE 802.3af and 802.3at switch blades
- Meets CNSS 5001 defined requirements for use in SCIF and SAPF environments

Additional Features

- The speakerphone function is enabled and protected with the TSG on-hook security.
- The headset port is enabled and protected with the TSG on-hook security.



TSG On-Hook
Security
Indicator
& Activation
Switch



The Polycom CX600 is a full-featured modified UC desktop phone, optimized for use with Microsoft Communications Server "14" environments that helps maximize productivity. Seamless integration with Microsoft Lync Server enhances user experience and provides easy setup and configuration. Built-in dual Gigabit Power over Ethernet (PoE) ports provide full-speed data connectivity between the network and a user's computer, to enable bandwidth-intensive applications on the user's desktop.



Specifications

User Interface

3.5-inch QVGA TFT 24-bit color graphical display
320 x 240 pixels
LED backlight with adjustable brightness
Backlight auto-dim when not in use

Handset and Headset

Wideband handset
Headset port
Optional Push to Talk handset

Speakerphone

Full-duplex speakerphone

LAN and PC Ports

2-port Ethernet switch
LAN Port 10/100/1000Mb RJ45
PC Port 10/100/1000Mb RJ45

Keys

12-button dial pad, volume up and volume down, 2-way navigation: up, down, select, home, previous, 2 soft keys and menu, mute/unmute

CODEC support

Microsoft RTAudio
G.722.1
G.711

Dimensions (H x W x D)

5.5" x 9.5" x 7.0"

Weight

2.5 lbs.

Temperatures

Operating 32 to 104° F (0 to 40° C)
Non-operating -40 to 185° F (-40 to 85° C)

Humidity

Operating 10 to 90% , noncondensing

Power

Power over Ethernet
100-240V Power Supply (sold separately)

LED indicators

Ringing, in call, hold, speaker, mute, voicemail, headset

Optimized for Microsoft Lync

Microsoft Lync Server 2013
Microsoft Lync Server 2010

Warranty

Standard 1 year parts and labor
Optional 3 year parts and labor

Options

Part Numbers

DTD-CX600-OPT-01
DTD-CX600-PTT-HS-01
DTD-GS60A24

Item Description

Push to Talk handset
Microphone removal
Power Supply

Contact us

GLOBAL HEADQUARTERS

CIS Secure Computing
43671 Trade Center Place, Suite 142
Dulles, VA 20166

Phone: 703-996-0500

Fax: 703-996-1111

eFax: fax@cissecure.com

<http://www.cissecure.com>